



Engineered for cooler running to handle longer high-speed hauls, the RL47A is all about helping your earthmovers get the job done faster and more efficiently.

Specially designed features on the shoulder blocks provide for extra heat dissipation in this critical area of the tread.

Precise grooves are strategically placed across the tread to effectively disperse heat from the tread area for faster, longer hauls.



The RL47A is available in four different compound options to meet the tough demands of specific applications.

A larger, flatter footprint distributes weight more evenly and provides excellent cut resistance and longer service life.

SIZES AND SPECIFICATIONS

SIZE	ITEM NO	STAR Mark	COMPOUND	GROOVE DEPTH 1/32	RIM SIZE	INFLATED DIMENSIONS (INCHES)		STATIC	STATIC	SHIP
						OVERALL DIAMETER	OVERALL WIDTH	LOADED RADIUS (IN)	LOADED WIDTH (IN)	WEIGHT (LBS)
2700R49	130147012	2 stars	СР	84	19.50 - 4.0	105.1	28.9	47.8	32.7	2,893
	130147009	2 stars	CP-S	84		105.1	28.9	47.8	32.7	2,888
	130147008	2 stars	HR	84		105.1	28.9	47.8	32.7	2,877
	130147007	2 stars	REG	84		105.1	28.9	47.8	32.7	2,881

Yokohama tires are subject to an ongoing development process. Yokohama Tire Canada reserves the right to change product specifications at any time without notice or obligation.

